Pure Science. Perfect Finish.



TECHNICAL DATA SHEET

Product Name: Jade Ceramic Coating - Ice

Part No.	Size	Unit	
IJICC-K	50 mL	1/Kit	
JICC-50	50 mL	12/Case	
JICC-1G	1 Gallon	4/Case	
JICC-5G	5 Gallon		



Description:

JADE CERAMIC COATING - ICE is a clear, nano crystalline coating that protects your vehicle from weather, chemicals, and UV rays while repelling water, dirt and other contaminants. Jade Ice applies a hard (7H), durable coating that is 2-3 micron thick and imparts a deep, reflective shine.

Directions:

Shake well and pour several drops to suede applicator. Apply to 3x3 sq. ft. area of vehicle using a cross-hatch pattern with slight overlap to level product. Allow the coating to cure for 5-10 minutes and gently remove excess product using a clean suede cloth or low nap microfiber towel. Do NOT allow coating to come in contact with water for 48 hours while curing. Apply additional coats with at least one hour between applications. Do NOT apply in direct sunlight or to a hot surface. Cure time is dependant on environmental conditions - test product on a small inconspicuous area first to gauge cure time.

General Info:



UHS (SRC) Paint



5-35°C 41-95°F







Cautions:

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation. Harmful if swallowed.

First Aid:

Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do NOT induce vomiting, call physician.

Technical Data:

Flash Point: 112-119 F (44 - 48 C)

Appearance: Clear, Colorless

Physical State: Liquid

Odor: Characteristic

Specific Gravity: 0.97 g/cm³, 8.11 lb/USGal @ 25 C